



บริษัท เทคโน ฟล็กซ์ จำกัด  
โทร. 02-399-2059 ถึง 63

- LINING** : inner tube of oil resistant synthetic rubber
- REINFORCEMENT** : four layers of steel wire wrapped in alternating directions
- COVER** : oil and weather resistant synthetic rubber
- APPEARANCE** : black color, wrapped surface or smooth surface ( 1/2"-1 1/4")
- TEMPERATURE RANGE** : -40°C ~ +100°C (-40°F ~ +212°F)
- IMPLEMENTATION STANDARDS** : EN 856 4SH Four Spiral Wire Hydraulic Rubber Hose



**EN 856 4SH Four Spiral Wire**

**FEATURE** : high temperature ,abrasion and ozone resistant, inflaming retarding and resisting heat

SIZE			Internal Diameter		Reinforcement Diameter		Outside diameter		Working Pressure	Burst Pressure	Bending Radius	Weight
Mm	Inch	Dash	I.D		R.D		O.D		Max. W.P	Min. B.P	Min. B.R	
			Min	Max	Min	Max	Min	Max	Bar	Bar	mm	kg/m
16	5/8"	-10	15.5	16.7	23.2	24.8	27.4	29.0	450	1800	250	1.10
19	3/4"	-12	18.6	19.8	27.6	29.2	31.4	33.0	420	1680	280	1.40
25	1"	-16	25.0	26.4	34.4	36.0	37.5	39.9	380	1520	340	2.00
32	1.1/4"	-20	31.4	33.0	40.9	42.9	43.9	47.1	325	1300	460	2.55
38	1.1/2"	-24	37.7	39.3	47.8	49.8	51.9	55.1	290	1160	560	3.05
51	2"	-32	50.4	52.0	62.2	64.2	66.5	69.7	250	1000	700	4.35